

GENERAL FEATURES

- 136 - 174 MHz, 50 - 5 W
- 450 - 520 MHz, 40 - 5 W
- 400 - 470 MHz, 40 - 5 W
- Repeater Operation
- Two-Digit LED Display
- 6 Illuminated Programmable Function Keys
- Programmable AUX I/O's
- RF Power Down Detect
- DTMF Front Panel PF Key Control (Analog Only)
- DTMF AUX Output Control (Analog Only)
- DTMF AUX Input Monitoring (Analog Only)
- Windows® PC Programming
- Flash Firmware Upgrading

DIGITAL - CONVENTIONAL MODE

- DMR Digital Air Interface
- 12.5 kHz Channels
- Mixed FM / Digital Operation
- Repeater Control Built-in
- 1 Color Code Repeater Control Built-in
- Conventional IP Network*1
- AIS IP console interface*1, *2
- AMBE+2™ VOCODER
- Call Interruption

FM MODES - GENERAL

- VHF: 25 & 12.5 kHz Channels
- UHF: 25 & 12.5 kHz Channels
- CW ID

FM CONVENTIONAL MODE

- 16 QT / DQT Repeater Control Built-in
- Hang Timer

*1: Requires Interface Box KTI-5 installed with the IP Network Software.
*2: AIS stands for Application Interface Standard, which is a voice/data communications protocol set by the DMR Association.

KTI-5
INTERFACE BOX



Main Specifications

GENERAL		TKR-D710	TKR-D810
Frequency Range	Type 1 Type 2	136-174 MHz -	450-520 MHz 400-470 MHz
Channel Spacing	Analog Digital	25* / 12.5 kHz 12.5 kHz	
Current Drain	Standby Receive Transmit	0.5 A 1.0 A 11.0A	
TX Power	50% Duty 100% Duty	50 W 25 W	40W 25 W
Frequency Stability		± 1.0 ppm	
Operating Voltage		13.6 V DC ± 15%	
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)	
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included	19 x 3 1/2 x 13 1/3 in (483 x 88 x 340 mm)	
Weight (net)		21.4 lb (9.7 kg)	
FCC ID	Type 1 Type 2	K44422300 -	K44452500 K44452501
IC Certification	Type 1 Type 2	282F-422300 -	- 282F-452501

RECEIVER		TKR-D710	TKR-D810
Sensitivity	Digital 12.5 kHz (3% BER) Digital 12.5 kHz (1% BER) Analog @ 12 dB SINAD	0.28 μV -4 dB μV (0.32 μV) 0.28 μV	
Selectivity	Analog @ 25*/12.5 kHz	83 dB / 77 dB	80 dB / 74 dB
FM Hum & Noise	Analog @ 25*/12.5 kHz	55 dB / 50 dB	
Intermodulation		80 dB	
Spurious Response Rejection		90 dB	
Audio Distortion (Ext. Speaker)		Less than 2.5 % 1000 Hz	
Audio Output (Ext. Speaker)		4 W (at 4 Ω, Less than 5 % distortion)	
TRANSMITTER			
RF Power Output		50-5 W	40-5 W
Modulation Limiting	Analog 25*/12.5 kHz	± 5.0 kHz / ± 2.5 kHz	
Spurious Response		80 dB	
FM Hum & Noise	Analog 25*/12.5 kHz	55 dB / 50 dB	
Modulation Distortion		Less than 1% at 1000 Hz	
Emission Designator		16K0F3E, 11K0F3E, 7K60FXD, 7K60FXE	

*25 kHz is not included in the models sold in the USA or US territories.
Measurements made per CAI measurement procedures (digital) and TIA-603 (analog); specifications are typical.
Due to advancements in technology, specifications are subject to change without notice.

AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows® is a registered trademarks of Microsoft Corporation.

KENWOOD

JVCKENWOOD USA Corporation
Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

www.kenwood.com/usa

JVCKENWOOD Canada Inc.

Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

www.kenwood.com/ca



ISO9001 Registered

JVCKENWOOD Corporation

ADS#01716 Printed in USA